



# PHONO BOX RS

Highend phono preamplifier

MSRP 899 € (incl. VAT)

- MM & MC capable
- True dual mono design
- Balanced XLR & unbalanced RCA In & Outputs
- Fully passive RIAA & DECCA equalisation
- Unique continously variable input impedance loading, matches every cartridge (adjustment even while playing)
- Superior low noise / low distortion
- Classy & elegant dip switches
- Metal casing protects against vibration and interference
- Faceplate silver or black

colour options:



**Input impedance:** Fixed 10 ohms or 47kohms, variable 10 - 1200 ohms  
**Load capacity switchable:** 100pF 200pF, 300pF, 420pF, 520pF  
**Output impedance:** 50 ohms  
**Gain, MM / MC:** RCA: 40, 50, 60 dB XLR: 46, 56, 66 dB  
**Signal to noise ratio:** 80dB (91dB - IEC -A)  
**THD:** < 0,019%  
**RIAA accuracy:** within 0,3dB/20Hz - 20kHz  
**Subsonic:** 20Hz / - 12dB  
**Input:** RCA & XLR  
**Output:** RCA & XLR-  
**Power supply:** +2x 18V/300mA DC; 220 - 240V, 50Hz  
**Power consumption:** 150mA DC < 1 watt standby  
**Dimensions W x H x D (T with sockets):** 206 x 72 x 200 (210)mm  
**Weight:** 2000g without power supply

## Reference class phono preamplifier with unique impedance control

This ultra low noise and distortion preamplifier is made for the audio connoisseur and offers not only breathtaking performance but is capable to adapt to virtually any phono cartridge through variable impedance control. Impedance adjustment can be done while playback! Due to use of best parts, like SSM2019 from Analog Devices as input stages and Linear Technology LT1010 as high current buffer stage, Phono Box RS delivers ultra low levels of distortion and noise. Its very low output impedance makes it insensitive to selection of interconnect cables and lengths. Fully passive RIAA and DECCA equalisation is selectable. Phono Box RS offers balanced XLR and unbalanced RCA inputs and



outputs. All in all vinyl playback will never have sounded as clear, detailed and smooth, than with this superlative phono stage!

